

1. Identification

Product identifier	American Safety MS-11CZ Buff Primer Part A
Other means of identification	
Product code	MS709R, MS-11CZ
Recommended use	Only for professional use. Primer.
Recommended restrictions	Uses other than the recommended use.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Distributed by	Holcim Solutions and Products US, LLC
Address	26 Century Boulevard, Suite 205 Nashville, TN 37214 American Safety Technologies is a Holcim Solutions and Products US, LLC brand.
Website	holcimast.com
Telephone Number	1-800-878-7876
Emergency Telephone Number	For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident: CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
	Specific target organ toxicity, repeated exposure	Category 1 (lungs)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Causes damage to organs (lungs) through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.
Storage	Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Epoxy resin (number average molecular weight \leq 700)	25068-38-6	15 - 40
Barium sulfate	7727-43-7	5 - 10
Talc	14807-96-6	5 - 10
Titanium Dioxide	13463-67-7	5 - 10
Trizinc bis(orthophosphate)	7779-90-0	5 - 10
1-Methoxy-2-propanol	107-98-2	1 - 5
2,2'-(Oxybis((methyl-2,1-ethanediyl)-oxymethylene))bisoxirane	41638-13-5	1 - 5
2-Ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate	15625-89-5	1 - 5
Bisphenol-a-diglycidyl ether polymer	25036-25-3	1 - 5
Wollastonite	13983-17-0	1 - 5
Methyl n-amyl ketone	110-43-0	0.5 - 5
Cumene	98-82-8	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1
Quartz (SiO ₂)	14808-60-7	0.1 - 1

Composition comments All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation	Move to fresh air. If not breathing, give artificial respiration. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides (COx). Phenols. Hydrocarbons. Metal oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Persons susceptible to allergic reactions should not handle this product. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	0.05 mg/m ³

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Barium sulfate (CAS 7727-43-7)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Cumene (CAS 98-82-8)	PEL	245 mg/m3 50 ppm	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm	
Methyl n-amyl ketone (CAS 110-43-0)	PEL	465 mg/m3 100 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.1 mg/m3 2.4 mppcf	Respirable. Respirable.
Talc (CAS 14807-96-6)	TWA	0.1 mg/m3 20 mppcf 2.4 mppcf	Respirable. Respirable.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	100 ppm	
	TWA	50 ppm	
Barium sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Cumene (CAS 98-82-8)	TWA	5 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Methyl n-amyl ketone (CAS 110-43-0)	TWA	50 ppm	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3 0.2 mg/m3	Respirable finescale particles Respirable nanoscale particles
Wollastonite (CAS 13983-17-0)	TWA	1 mg/m3	Inhalable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Cumene (CAS 98-82-8)	IDLH	0.9 % 900 ppm
Ethylbenzene (CAS 100-41-4)	IDLH	0.8 % 800 ppm
Methyl n-amyl ketone (CAS 110-43-0)	IDLH	1.1 % 800 ppm

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Quartz (SiO ₂) (CAS 14808-60-7)	IDLH	50 mg/m ³
Talc (CAS 14807-96-6)	IDLH	1000 mg/m ³
Titanium Dioxide (CAS 13463-67-7)	IDLH	5000 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	540 mg/m ³	
		150 ppm	
	TWA	360 mg/m ³	
Barium sulfate (CAS 7727-43-7)	TWA	100 ppm	Respirable.
		5 mg/m ³	
Cumene (CAS 98-82-8)	TWA	10 mg/m ³	Total
		245 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	50 ppm	
		545 mg/m ³	
		125 ppm	
Methyl n-amyl ketone (CAS 110-43-0)	TWA	435 mg/m ³	
		100 ppm	
		465 mg/m ³	
Quartz (SiO ₂) (CAS 14808-60-7)	TWA	100 ppm	Respirable dust.
		0.05 mg/m ³	
Talc (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable.

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

Components	Type	Value
2-Ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate (CAS 15625-89-5)	TWA	1 mg/m ³

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	150 mg/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

1-Methoxy-2-propanol (CAS 107-98-2) Can be absorbed through the skin.
 Cumene (CAS 98-82-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US WEEL Guides: Skin designation

2-Ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate (CAS 15625-89-5) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with organic vapor cartridge and full facepiece. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Liquid.

Color Buff.

Odor Mild.

Odor threshold Not determined.

pH Not determined.

Melting point/freezing point Not determined.

Initial boiling point and boiling range > 240 °F (> 115.56 °C)

Flash point > 101 °F (> 38.33 °C) Seta closed cup.

Evaporation rate Not determined.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not determined.

Explosive limit - upper (%) Not determined.

Vapor pressure Not determined.

Vapor density 3.1 (Air = 1)

Relative density 2.08 (Water = 1)

Solubility(ies)

Solubility (water) Not soluble.

Partition coefficient (n-octanol/water) Not applicable, product is a mixture.

Auto-ignition temperature 1094 °F (590 °C) estimated

Decomposition temperature	Not determined.
Viscosity	Not available.
Other information	
Density	2.08 g/cm ³
Explosive properties	Not explosive.
Kinematic viscosity	Not determined.
Oxidizing properties	Not oxidizing.
VOC	121 g/l (EPA Method 24)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Aluminum. Phosphorus.
Hazardous decomposition products	In the event of fire: See Section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
1-Methoxy-2-propanol (CAS 107-98-2)		
Acute		
Dermal		
LD50	Rabbit	13000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
2,2'-(Oxybis((methyl-2,1-ethanediyl)-oxymethylene))bisoxirane (CAS 41638-13-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg (No deaths occurred at this concentration)
Oral		
LD50	Rat	> 2000 mg/kg (No deaths occurred at this concentration)
2-Ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate (CAS 15625-89-5)		
Acute		
Dermal		
LD50	-	> 2000 mg/kg
Oral		
LD50	-	3680 mg/kg

Components	Species	Test Results
Barium sulfate (CAS 7727-43-7)		
Acute		
Oral		
LD50	Rat	> 5000 mg/kg
Epoxy resin (number average molecular weight ≤ 700) (CAS 25068-38-6)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Oral		
LD50	Rat	15000 mg/kg
Ethylbenzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	15400 mg/kg
Inhalation		
LC50	Rat	17.4 mg/l, 4 hours
Oral		
LD50	Rat	3500 - 4700 mg/kg
Methyl n-amyl ketone (CAS 110-43-0)		
Acute		
Dermal		
LD50	Rabbit	12600 mg/kg
Oral		
LD50	Rat	1600 mg/kg
Quartz (SiO ₂) (CAS 14808-60-7)		
Chronic		
Inhalation		
LOEC	Human	0.0563 mg/m ³
Talc (CAS 14807-96-6)		
Acute		
Oral		
LD50	Rat	> 5000 mg/kg
Titanium Dioxide (CAS 13463-67-7)		
Acute		
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans. Due to the form of the product, exposure to the potentially carcinogenic components is not expected. Titanium dioxide is considered carcinogenic only when in an inhalable powdered form. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
2-Ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate (CAS 15625-89-5)	2B Possibly carcinogenic to humans.	
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.	

Ethylbenzene (CAS 100-41-4)
 Quartz (SiO₂) (CAS 14808-60-7)
 Talc (CAS 14807-96-6)
 Titanium Dioxide (CAS 13463-67-7)
 Wollastonite (CAS 13983-17-0)

2B Possibly carcinogenic to humans.
 1 Carcinogenic to humans.
 3 Not classifiable as to carcinogenicity to humans.
 2B Possibly carcinogenic to humans.
 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Cumene (CAS 98-82-8)
 Quartz (SiO₂) (CAS 14808-60-7)

Reasonably Anticipated to be a Human Carcinogen.
 Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO₂) (CAS 14808-60-7)

Cancer

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure Not classified.
Specific target organ toxicity - repeated exposure Causes damage to organs (lungs) through prolonged or repeated exposure.
Aspiration hazard Not an aspiration hazard.
Chronic effects Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
2,2'-(Oxybis((methyl-2,1-ethanediy)l)-oxymethylene))bisoxirane (CAS 41638-13-5)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna 90 mg/l, 48 hours (OECD 202)
Fish	LC50	Leuciscus idus 67 mg/l, 96 hours
2-Ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate (CAS 15625-89-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Leuciscus idus 1.47 mg/l, 96 hours
Barium sulfate (CAS 7727-43-7)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Tubificid worm (Tubifex tubifex) 28.61 - 38.03 mg/l, 48 hours
Ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 1.81 - 2.38 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4.2 mg/l, 96 hours
<i>Chronic</i>		
Crustacea	EC50	Ceriodaphnia dubia 3.6 mg/l, 7 days
Methyl n-amyl ketone (CAS 110-43-0)		
Aquatic		
<i>Acute</i>		
Algae	EC50	Selenastrum capricornutum 98.2 mg/l, 72 Hours
Crustacea	EC50	Daphnia magna > 90.1 mg/l, 48 Hours
Fish	LC50	Pimephales promelas 131 mg/l, 96 Hours
<i>Chronic</i>		
Algae	NOEC	Selenastrum 42.7 mg/l, 72 Hours

Components	Species	Test Results
Titanium Dioxide (CAS 13463-67-7)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna > 100 mg/l, 48 Hours
Fish	LL50	Oryzias latipes > 100 mg/l, 96 Hours
Trizinc bis(orthophosphate) (CAS 7779-90-0)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Oncorhynchus mykiss 169 µg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1-Methoxy-2-propanol (CAS 107-98-2)	-0.49
Cumene (CAS 98-82-8)	3.66
Ethylbenzene (CAS 100-41-4)	3.15
Methyl n-amyl ketone (CAS 110-43-0)	1.98

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential. This product contains one or more substances identified as hazardous air pollutants (HAPs) per the US Federal Clean Air Act (see section 15).

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

Non-bulk: Not hazardous for transport under 49 CFR exceptions 173.150 (f) (1, 2, 3).

DOT BULK

BULK

UN number UN1263

UN proper shipping name Paint

Transport hazard class(es)

Class 3

Subsidiary hazard -

Label(s) 3

Packing group III

Environmental hazards

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. DOT (Road/Rail): Non-bulk shipments of this material are non-regulated for domestic ground transportation when they meet the requirements of 49 CFR 171.4(c).

Special provisions 367, B1, B52, B131, IB3, T2, TP1, TP29

Packaging exceptions 150

Packaging non bulk 173

Packaging bulk 242

IATA

UN number UN1263
UN proper shipping name Paint
Transport hazard class(es)
Class 3
Subsidiary hazard -
Packing group III
Environmental hazards Yes
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1263
UN proper shipping name PAINT
Transport hazard class(es)
Class 3
Subsidiary hazard -
Packing group III
Environmental hazards
Marine pollutant Yes
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8)	Listed
Ethylbenzene (CAS 100-41-4)	Listed
Trizinc bis(orthophosphate) (CAS 7779-90-0)	Listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO ₂) (CAS 14808-60-7)	Cancer lung effects immune system effects kidney effects
---	---

Toxic Substances Control Act (TSCA) One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Respiratory or skin sensitization
 Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Cumene	98-82-8	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Trizinc bis(orthophosphate)	7779-90-0	5 - 10

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

Methyl n-amyl ketone (CAS 110-43-0)

Other Flavoring Substances with OSHA PEL's

US state regulations**US. Massachusetts RTK - Substance List**

1-Methoxy-2-propanol (CAS 107-98-2)

Barium sulfate (CAS 7727-43-7)

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Methyl n-amyl ketone (CAS 110-43-0)

Quartz (SiO₂) (CAS 14808-60-7)

Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

1-Methoxy-2-propanol (CAS 107-98-2)

Barium sulfate (CAS 7727-43-7)

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Methyl n-amyl ketone (CAS 110-43-0)

Quartz (SiO₂) (CAS 14808-60-7)

Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

Trizinc bis(orthophosphate) (CAS 7779-90-0)

US. Pennsylvania Worker and Community Right-to-Know Law

1-Methoxy-2-propanol (CAS 107-98-2)

Barium sulfate (CAS 7727-43-7)

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Methyl n-amyl ketone (CAS 110-43-0)

Quartz (SiO₂) (CAS 14808-60-7)

Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

Trizinc bis(orthophosphate) (CAS 7779-90-0)

US. Rhode Island RTK

1-Methoxy-2-propanol (CAS 107-98-2)

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Methyl n-amyl ketone (CAS 110-43-0)

Quartz (SiO₂) (CAS 14808-60-7)

Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

California Proposition 65

WARNING: This product can expose you to chemicals including 1,3-Butadiene, 2-Ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate, Acrylonitrile, Benzene, Cumene, Ethylbenzene, Naphthalene, and Styrene, which are known to the State of California to cause cancer, and 1,3-Butadiene, Benzene, Methanol, and Toluene, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,3-Butadiene (CAS 106-99-0)

Listed: April 1, 1988

2-Ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate (CAS 15625-89-5)	Listed: December 17, 2021
Acrylonitrile (CAS 107-13-1)	Listed: July 1, 1987
Benzene (CAS 71-43-2)	Listed: February 27, 1987
Cumene (CAS 98-82-8)	Listed: April 6, 2010
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988
Naphthalene (CAS 91-20-3)	Listed: April 19, 2002
Styrene (CAS 100-42-5)	Listed: April 22, 2016

California Proposition 65 - CRT: Listed date/Developmental toxin

1,3-Butadiene (CAS 106-99-0)	Listed: April 16, 2004
Benzene (CAS 71-43-2)	Listed: December 26, 1997
Methanol (CAS 67-56-1)	Listed: March 16, 2012
Toluene (CAS 108-88-3)	Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Female reproductive toxin

1,3-Butadiene (CAS 106-99-0)	Listed: April 16, 2004
------------------------------	------------------------

California Proposition 65 - CRT: Listed date/Male reproductive toxin

1,3-Butadiene (CAS 106-99-0)	Listed: April 16, 2004
Benzene (CAS 71-43-2)	Listed: December 26, 1997

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-October-2024

Revision date -

Version # 01

HMIS® ratings Health: 3*
Flammability: 3
Physical hazard: 0

Disclaimer Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.