

SAFETY DATA SHEET

1. Identification

Product identifier American Safety - MS200 Acrylic Epoxy Coating White Part A

Other means of identification

Product code MS203K, MS203R, MS204K

Recommended use Professional Use Only. Marine and Industrial Coating.

Recommended restrictions Uses other than the recommended use.

Manufacturer/Importer/Supplier/Distributor information

Distributed by Amrize Building Envelope LLC

Address 26 Century Boulevard, Suite 205
Nashville, TN 37214

American Safety Technologies is part of the Amrize family of brands.

Website astcoatings.com

Telephone Number 1-800-878-7876

Emergency Telephone Number For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:

CHEMTREC within USA and Canada: 1-800-424-9300

CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Hazards for the product as sold

Physical hazards Flammable liquids Category 3

Hazards for the product as sold

Health hazards

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Sensitization, skin	Category 1
Carcinogenicity	Category 1B
Reproductive toxicity (fertility, the unborn child)	Category 2
Specific target organ toxicity, single exposure	Category 3 narcotic effects
Aspiration hazard	Category 1

Hazards for the product as sold

Environmental hazards

Hazardous to the aquatic environment, acute hazard	Category 2
Hazardous to the aquatic environment, long-term hazard	Category 3

Hazards for the product as sold

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of damaging the unborn child. Suspected of damaging fertility. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

No additional hazards are known to be associated with the expected conditions of use at the time of publication. This document does not address hazards that may arise from uses not reasonably anticipated by the manufacturer.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	10 - 30
Methyl n-amyl ketone	110-43-0	7 - 13
Oxirane, mono-[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	7 - 13
Solvent naphtha (petroleum), light aromatic	64742-95-6	7 - 13
1-Methoxy-2-propanol	107-98-2	5 - 10
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer	25085-99-8	5 - 10
1,2,4-Trimethylbenzene	95-63-6	1 - 5
2-Methoxy-1-methylethyl acetate	108-65-6	1 - 5
Hexyl acetate	142-92-7	1 - 5
Cumene	98-82-8	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1
Trimethylolpropane	77-99-6	0.1 - 1

Composition comments

All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Call a poison center or doctor/physician if you feel unwell.

Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides. Sodium oxides. Silicon oxides. Potassium oxides. Aluminum oxides. Titanium dioxide.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Persons susceptible to allergic reactions should not handle this product.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Cumene (CAS 98-82-8)	PEL	245 mg/m3 50 ppm	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm	
Methyl n-amyl ketone (CAS 110-43-0)	PEL	465 mg/m3 100 ppm	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	10 ppm	
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	100 ppm	
	TWA	50 ppm	
Cumene (CAS 98-82-8)	TWA	5 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Methyl n-amyl ketone (CAS 110-43-0)	TWA	50 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3 0.2 mg/m3	Respirable finescale particles Respirable nanoscale particles

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Cumene (CAS 98-82-8)	IDLH	900 ppm
Ethylbenzene (CAS 100-41-4)	IDLH	800 ppm
Methyl n-amyl ketone (CAS 110-43-0)	IDLH	800 ppm

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Titanium dioxide (CAS 13463-67-7)	IDLH	5000 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3 25 ppm
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	540 mg/m3 150 ppm
	TWA	360 mg/m3 100 ppm
Cumene (CAS 98-82-8)	TWA	245 mg/m3 50 ppm
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3 125 ppm
	TWA	435 mg/m3 100 ppm
Methyl n-amyl ketone (CAS 110-43-0)	TWA	465 mg/m3 100 ppm

US. OARS. Workplace Environmental Exposure Level (WEEL) Guide

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	50 ppm

Biological limit values**ACGIH Biological Exposure Indices (BEI)**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	150 mg/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

1-Methoxy-2-propanol (CAS 107-98-2)	Can be absorbed through the skin.
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Cumene (CAS 98-82-8)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8)	Skin designation applies.
----------------------	---------------------------

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

US. NIOSH: Pocket Guide to Chemical Hazards

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)	Can be absorbed through the skin.
----------------------	-----------------------------------

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Glove material: Nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.06 mm. Glove material: Polyvinyl acetate. Use gloves with breakthrough time of 240 minutes. Minimum glove thickness 0.07 mm. Glove material: Latex. Use gloves with breakthrough time of 240 minutes. Minimum glove thickness 0.12 mm. Glove material: Polyvinyl chloride. Use gloves with breakthrough time of 240 minutes. Minimum glove thickness 0.1 mm. Suitable gloves can be recommended by the glove supplier.
Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with organic vapor cartridge and full facepiece. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Physical state	Liquid.
Form	Viscous liquid.
Color	White.
Odor	Strong solvent.
Odor threshold	Property has not been measured.
Melting point/freezing point	89.6 °F (32 °C)
Boiling point or initial boiling point and boiling range	248 °F (120 °C)
Flammability	Flammable liquid.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Flammable.
Explosive limit - upper (%)	Flammable.
Flash point	102 °F (38.89 °C) Pensky-Martens Closed Cup
Auto-ignition temperature	Not ignitable.
Decomposition temperature	Property has not been measured.
pH	5 <7
pH concentration	Property has not been measured.
Kinematic viscosity	Property has not been measured.
Kinematic viscosity temp	Property has not been measured.
Solubility	
Solubility (water)	Moderately soluble
Partition coefficient (n-octanol/water)	Not applicable, product is a mixture.

Vapor pressure	8 mmHg
Vapor pressure temp.	71.6 °F (22 °C)
Density and/or relative density	
Density	9.82 lb/gal
Relative density	0.96
Relative density temperature	68 °F (20 °C)
Vapor density	3.94
Vapor density temp.	68 °F (20 °C)
Particle characteristics	Property has not been measured.
Particle size	Not applicable, material is a liquid.
Other information	
Dynamic viscosity	Property has not been measured.
Dynamic viscosity temp	Property has not been measured.
Evaporation rate	Property has not been measured.
Explosive properties	Not explosive.
Flammability	Flammable.
Oxidizing properties	Not oxidizing.
Viscosity	Property has not been measured.
VOC	3.4 lb/gal (EPA Method 24)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known. In the event of fire: See Section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Oral		
LD50	Rat	2720 - 3960 mg/kg
1-Methoxy-2-propanol (CAS 107-98-2)		
Acute		
Dermal		
LD50	Rabbit	13000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Oral		
LD50	Rat	> 8532 mg/kg
Cumene (CAS 98-82-8)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg, 24 Hours
Inhalation		
LC50	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	2910 mg/kg
Ethylbenzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	15400 mg/kg
Inhalation		
LC50	Rat	17.4 mg/l, 4 hours
Oral		
LD50	Rat	3500 - 4700 mg/kg
Hexyl acetate (CAS 142-92-7)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Oral		
LD50	Rat	36100 mg/kg
Methyl n-amyl ketone (CAS 110-43-0)		
Acute		
Dermal		
LD50	Rabbit	12600 mg/kg
Oral		
LD50	Rat	1600 mg/kg
Titanium dioxide (CAS 13463-67-7)		
Acute		
Oral		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
Trimethylolpropane (CAS 77-99-6)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
<i>Mist</i>		
LC50	Rat	> 0.85 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	May cause cancer. Titanium dioxide is considered carcinogenic only when in an inhalable powdered form.	

IARC Monographs. Overall Evaluation of Carcinogenicity

Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Solvent naphtha (petroleum), light aromatic (CAS 64742-95-6)	3 Not classifiable as to carcinogenicity to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Cumene (CAS 98-82-8)	Reasonably Anticipated to be a Human Carcinogen.
----------------------	--

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Fathead minnow (Pimephales promelas)	7.72 mg/l, 96 hours
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Oryzias latipes	> 100 mg/l, 96 hours

Components	Species	Test Results
Cumene (CAS 98-82-8)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.7 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 1.81 - 2.38 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4.2 mg/l, 96 hours
<i>Chronic</i>		
Crustacea	EC50	Ceriodaphnia dubia 3.6 mg/l, 7 days
Hexyl acetate (CAS 142-92-7)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 4.4 mg/l, 96 hours
Methyl n-amyl ketone (CAS 110-43-0)		
Aquatic		
<i>Acute</i>		
Algae	EC50	Selenastrum capricornutum 98.2 mg/l, 72 Hours
Crustacea	EC50	Daphnia magna > 90.1 mg/l, 48 Hours
Fish	LC50	Pimephales promelas 131 mg/l, 96 Hours
<i>Chronic</i>		
Algae	NOEC	Selenastrum 42.7 mg/l, 72 Hours
Solvent naphtha (petroleum), light aromatic (CAS 64742-95-6)		
Aquatic		
<i>Acute</i>		
Crustacea	EL50	Daphnia 4.5 mg/l, 48 hours
Fish	LL50	Oncorhynchus mykiss 10 mg/l, 96 hours
Titanium dioxide (CAS 13463-67-7)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna > 100 mg/l, 48 Hours
Fish	LL50	Oryzias latipes > 100 mg/l, 96 Hours
Trimethylolpropane (CAS 77-99-6)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna 13000 mg/l, 48 hours
Fish	LC50	Oryzias latipes > 1000 mg/l, 96 Hours
<i>Chronic</i>		
Crustacea	NOEC	Daphnia magna > 1000 mg/l, 21 days

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1,2,4-Trimethylbenzene (CAS 95-63-6)	3.78
1-Methoxy-2-propanol (CAS 107-98-2)	-0.49
Cumene (CAS 98-82-8)	3.66
Ethylbenzene (CAS 100-41-4)	3.15

Partition coefficient n-octanol / water (log Kow)

Methyl n-amyl ketone (CAS 110-43-0)

1.98

Mobility in soil No data available.**Other adverse effects** This product contains one or more substances identified as hazardous air pollutants (HAPs) per the US Federal Clean Air Act (see section 15).**13. Disposal considerations****Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.**Local disposal regulations** Dispose in accordance with all applicable regulations.**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.**14. Transport information****DOT**

Not regulated as dangerous goods.

Non-bulk: Not hazardous for transport under 49 CFR exceptions 173.150 (f) (1, 2, 3).

DOT BULK**BULK****UN number** UN1263**UN proper shipping name** Paint**Transport hazard class(es)****Class** 3**Subsidiary hazard** -**Label(s)** 3**Packing group** III**Environmental hazards****Marine pollutant** Yes**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. DOT (Road/Rail): Non-bulk shipments of this material are non-regulated for domestic ground transportation when they meet the requirements of 49 CFR 171.4(c).**Special provisions** 367, B1, B52, B131, IB3, T2, TP1, TP29**Packaging exceptions** 150**Packaging non bulk** 173**Packaging bulk** 242**IATA****UN number** UN1263**UN proper shipping name** Paint**Transport hazard class(es)****Class** 3**Subsidiary hazard** -**Packing group** III**Environmental hazards** Yes**ERG Code** 3L**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**IMDG****UN number** UN1263**UN proper shipping name** PAINT**Transport hazard class(es)****Class** 3**Subsidiary hazard** -

Packing group III
Environmental hazards
Marine pollutant Yes
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to IMO instruments Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cumene (CAS 98-82-8) Listed

Ethylbenzene (CAS 100-41-4) Listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Respiratory or skin sensitization
 Carcinogenicity
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)
 Aspiration hazard

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Cumene	98-82-8	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Methyl n-amyl ketone (CAS 110-43-0)

Other Flavoring Substances with OSHA PEL's

US state regulations

US. Massachusetts RTK - Substance List

1-Methoxy-2-propanol (CAS 107-98-2)

1,2,4-Trimethylbenzene (CAS 95-63-6)

Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Methyl n-amyl ketone (CAS 110-43-0)
Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

1-Methoxy-2-propanol (CAS 107-98-2)
1,2,4-Trimethylbenzene (CAS 95-63-6)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Methyl n-amyl ketone (CAS 110-43-0)
Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1-Methoxy-2-propanol (CAS 107-98-2)
1,2,4-Trimethylbenzene (CAS 95-63-6)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Methyl n-amyl ketone (CAS 110-43-0)
Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

1-Methoxy-2-propanol (CAS 107-98-2)
1,2,4-Trimethylbenzene (CAS 95-63-6)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Methyl n-amyl ketone (CAS 110-43-0)
Titanium dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, Cumene, and Ethylbenzene, which are known to the State of California to cause cancer, and Benzene and Toluene, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2)	Listed: February 27, 1987
Cumene (CAS 98-82-8)	Listed: April 6, 2010
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004

California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
Toluene (CAS 108-88-3)	Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 07-July-2025
Revision date -
Version # 01
HMIS® ratings Health: 3*
Flammability: 2
Physical hazard: 0

Disclaimer Amrize Building Envelope LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.